

acc. to 29 CFR 1910.1200 App D

WAFER APPLE ORKIN ECO

Version number: GHS 1.0

SECTION 1: Identification

1.1 Product identifier

Trade name Alternative number(s) WAFER APPLE ORKIN ECO

Date of compilation: 2020-12-31

WFR-APPLE-ORKIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

General use

1.3 Details of the supplier of the safety data sheet

ORKIN 5840 FALBOURNE STREET MISSISSAUGA , ON L5R 4B5 1-905-761-0041

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Section Hazard class		Hazard class and cat- egory	Hazard statement	
A.4S	A.4S skin sensitization		Skin Sens. 1	H317	

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning
- Pictograms

GHS07

H317



- Hazard statements

May cause an allergic skin reaction.

- Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P321	Specific treatment (see on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to industrial combustion plant.



acc. to 29 CFR 1910.1200 App D

WAFER APPLE ORKIN ECO

Version number: GHS 1.0

Date of compilation: 2020-12-31

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

IUPAC name	Identifier	Wt%	Classification acc. to GHS
1,3-diethyl propanedioate	CAS No 105-53-3	5 - < 10	Flam. Liq. 4 / H227
2-methylpentane-2,4-diol	CAS No 107-41-5	5 - < 10	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319
prop-2-en-1-yl heptanoate	CAS No 142-19-8	1 - < 5	Flam. Liq. 4 / H227
2-methyl-3-[4-(propan-2-yl)phenyl]propanal	CAS No 103-95-7	1 - < 5	Flam. Liq. 4 / H227
ethyl acetate	CAS No 141-78-6	1-<5	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225
ethyl 3-oxobutanoate	CAS No 141-97-9	1 - < 5	Flam. Liq. 4 / H227
3-methylbutyl 3-methylbutanoate	CAS No 659-70-1	1 - < 5	Flam. Liq. 4 / H227
1-(3,5,5,6,8,8-hexamethyl-5,6,7,8-tetrahy- dronaphthalen-2-yl)ethan-1-one	CAS No 112-70-9 1506-02-1	1-<5	Acute Tox. 4 / H302
(4R)-1-methyl-4-(prop-1-en-2-yl)cyclohex-1-ene	CAS No 5989-27-5	<1	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Flam. Liq. 3 / H226
2,6-dimethylphenol	CAS No 93-04-9 576-26-1	<1	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Skin Corr. 1B / H314

For full text of abbreviations: see SECTION 16.



Version number: GHS 1.0

Date of compilation: 2020-12-31

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



Version number: GHS 1.0

Date of compilation: 2020-12-31

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.



Version number: GHS 1.0

Date of compilation: 2020-12-31

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Coun- try	Name of sub- stance	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	2-methylpentane- 2,4-diol	107-41-5	PEL (CA)					25	125		Cal/ OSHA PEL
US	2-methylpentane- 2,4-diol	107-41-5	REL					25	125		NIOSH REL
US	2-methylpentane- 2,4-diol	107-41-5	TLV®				10			i, aero- sol	ACGIH® 2019
US	2-methylpentane- 2,4-diol	107-41-5	TLV®	25		50				vap	ACGIH® 2019
US	ethyl acetate	141-78-6	PEL (CA)	400	1,400						Cal/ OSHA PEL
US	ethyl acetate	141-78-6	REL	400 (10 h)	1,400 (10 h)						NIOSH REL
US	ethyl acetate	141-78-6	TLV®	400							ACGIH® 2019
US	ethyl acetate	141-78-6	PEL	400	1,400						29 CFR 1910.100 0
US	2,6-dimethylphenol	576-26-1	TLV®	1						iv	ACGIH® 2019

Notation

 aerosol
 as aerosols

 Ceiling-C
 ceiling value is a limit value above which exposure should not occur

 i
 inhalable fraction

 iv
 inhalable fraction and vapor

 STEL
 short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

 TWA
 time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

 vap
 as vapors

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



Version number: GHS 1.0

Date of compilation: 2020-12-31

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid		
Color	various		
Odor	characteristic		

Other safety parameters

pH (value)	not determined		
Melting point/freezing point	not determined		
Initial boiling point and boiling range	170.8 °F at 101.3 kPa		
Flash point	201 °F		
Evaporation rate	not determined		
Flammability (solid, gas)	not relevant, (fluid)		

Explosive limits



Version number: GHS 1.0

Date of compilation: 2020-12-31

- Lower explosion limit (LEL)	2.2 vol%		
- Upper explosion limit (UEL)	11.5 vol%		
Vapor pressure	9.187 kPa at 291.8 K		
Density	not determined		
Vapor density	this information is not available		
Relative density	information on this property is not available		
Solubility(ies)	not determined		
Partition coefficient			
- n-octanol/water (log KOW)	this information is not available		

Auto-ignition temperature	482 °F (auto-ignition temperature (liquids and gases))		
Viscosity	not determined		
Explosive properties	none		
Oxidizing properties	none		

9.2 Other information

Solvent content	97.07 %		
Solid content	2.934 %		
Temperature class (USA, acc. to NEC 500)	T2C (maximum permissible surface temperature on the equip- ment: 230°C)		

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.



Version number: GHS 1.0

Date of compilation: 2020-12-31

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WAFER APPLE ORKIN ECO

Version number: GHS 1.0

Date of compilation: 2020-12-31

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

- **12.2 Persistence and degradability** Data are not available.
- **12.3 Bioaccumulative potential** Data are not available.
- **12.4 Mobility in soil** Data are not available.
- **12.5 Results of PBT and vPvB assessment** Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

14.2 UN proper shipping name

Technical name (hazardous ingredients)

14.3 Transport hazard class(es)

Class

- 14.4 Packing group
- 14.5 Environmental hazards

Environmentally hazardous substance (aquatic environment)

3082

Environmentally hazardous substance, liquid, n.o.s. TRIDECYL ALCOHOL, ALLYL HEPTOATE

9 (environmentally hazardous)

III (substance presenting low danger)

hazardous to the aquatic environment TRIDECYL ALCOHOL, ALLYL HEPTOATE



Version number: GHS 1.0

Date of compilation: 2020-12-31

14.6 Special precautions for user There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)				
Index number	3082			
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.			
- Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, li- quid, n.o.s., (contains: TRIDECYL ALCOHOL, ALLYL HEPTOATE), 9, III			
- Reportable quantity (RQ)	359,738 lbs (163,321 kg) (ETHYL ACETATE) (METHYL OCTIN CAR- BONATE)			
Class	9			
Packing group	III			
Danger label(s)	9, fish and tree			
Environmental hazards	Yes (hazardous to the aquatic environment)			
Special provisions (SP)	8, 146, 173, 335, IB3, T4, TP1, TP29			
ERG No	171			
International Maritime Dangerous Goods Code (I	IMDG)			
UN number	3082			
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LI- QUID, N.O.S.			
Class	9			
Marine pollutant	Yes (hazardous to the aquatic environment)			
Packing group	III			
Danger label(s)	9, fish and tree			
Special provisions (SP)	274, 335, 969			
Excepted quantities (EQ)	E1			
Limited quantities (LQ)	5 L			
EmS	F-A, S-F			



Version number: GHS 1.0

WAFER APPLE ORKIN ECO

Date of compilation: 2020-12-31

	•					
Stowage category	Α					
International Civil Aviation Organization	ternational Civil Aviation Organization (ICAO-IATA/DGR)					
UN number	3082					
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.					
Class	9					
Environmental hazards	Yes (hazardous to the aquatic environment)					
Packing group	III					
Danger label(s)	9, fish and tree					
Special provisions (SP)	A97, A158, A197					
Excepted quantities (EQ)	E1					
Limited quantities (LQ)	30 kg					

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ETHYL ACETATE	141-78-6		4	5000 (2270)

Legend

"4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
ethyl acetate	141-78-6		CDC 4th National Exposure Report
(4R)-1-methyl-4-(prop-1-en-2-yl)cyclohex-1-ene	5989-27-5		EU Fragrance Allergens
2,6-dimethylphenol	105-67-9		CWA 303(c) CWA 303(d)



Version number: GHS 1.0

Date of compilation: 2020-12-31

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concen- tration Threshold
ethyl acetate	141-78-6				1.0 %
2,6-dimethylphenol	1300-71-6				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
ETHYL ACETATE	141-78-6	A, O	
HEXYLENE GLYCOL	107-41-5	А	
TRIDECYL ALCOHOL		А	dust

Legend

A

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physic-

dust

al Agents and Biological Exposure Indices for 1992-93", available from ACGIH If the substance poses an airborne particulate exposure hazard, the substance is followed by the word "dust." Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Oc-0 cupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
1,3-diethyl propanedioate	105-53-3		F2
(4R)-1-methyl-4-(prop-1-en-2-yl)cyclohex-1-ene	138-86-3		F2
ethyl acetate	141-78-6		F3
2-methylpentane-2,4-diol	107-41-5		F2
2,6-dimethylphenol	1300-71-6		

Legend

F2 Flammable - Second Degree

F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ACETIC ACID ETHYL ESTER	141-78-6	E
BUTANOIC ACID, 3-OXO-, ETHYL ESTER	141-97-9	
2,4-PENTANEDIOL, 2-METHYL-	107-41-5	
PHENOL, DIMETHYL-	1300-71-6	E

Legend

Environmental hazard

F



Version number: GHS 1.0

Date of compilation: 2020-12-31

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ETHYL ACETATE	141-78-6	T, F
HEXYLENE GLYCOL	107-41-5	Т

Legend F

Flammability (NFPA®) Toxicity (ACGIH®)

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or resid- ual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WAFER APPLE ORKIN ECO

Version number: GHS 1.0

Date of compilation: 2020-12-31

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presenta-tions/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
IUPAC	International Union of Pure and Applied Chemistry
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

WAFER APPLE ORKIN ECO

Version number: GHS 1.0

Date of compilation: 2020-12-31

Abbr.	Descriptions of used abbreviations
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.



acc. to 29 CFR 1910.1200 App D

WAFER APPLE ORKIN ECO

Version number: GHS 1.0

Date of compilation: 2020-12-31

Code	Text
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.